

Kållered 2024-09-24

## This document summarizes the software updates for RCFD from v 5 to v.7

You can easily check the software in the parameter menu on the display, parameter 55, see appendix B in the manual

## Update for RCFD230C, Ver 7

- 1. TP35492
- Bug: Setpoint not correctly calculated in 2-pipe mode
- Fixed in version 7, Now works exactly as in 4 pipe mode, The calculated setpoint readout in register 30 is also fixed. Both 2 pipe and 4 pipe mode is also updated so that hysteresis is symmetrical to calculated setpoint. I nearlier version it was setpoint + hysteresis for cooling and setpoint hysteresis for heating instead of setpoint +- hysteresis/2.

## Update for RCFD230C, Ver 6

- 2. TP28356
- Bug: Power cycle inits to Off and not Standby as written in manual.
- Fixed in version 6, goes to standby after power cycle, if not presence detector is configured and active, then it goes to occupied. Manual updated for version 6 to describe this change.
- 3. TP30671
- Improvement: Possibility to hide the fan symbol in the display
- When configuring the unit for no fans, the fan symbol is hidden in the display. Manual updated describing how in chapter 2.4
- 4. TP30839
- Bug: Setpoint read out from inpout register 29 did not include deadband (prev called hysteresis)
- Added a new inpiut register 30 with the correct function including deadband
- Leaving register 29 as it is with a new description in manual
- 5. TP22329
- Timeout for parameter menu is changed from 5 seconds to 15 seconds. Mainly to simplify the dialog with support and not having the meny timing out

## Update for RCFD230C, Ver 5

1. TP22457

Controller not acting with the correct deadband and hysteresis according to manual.

Corrected, and also changed the naming in manual (version 6 manual) so that what was called hysteresis is now more correctly called deadband, and the DeltaT is called hysteresis.

AB Regin

**Head office Sweden** 

Tel: +46 (0)31- 720 02 00 E-mail: info@regin.se Box 116

428 22 Kållered

Visiting address: Bangårdsvägen 35 428 36 Kållered

